

Triumph TR6

The TR6 has been created for the man who knows what motoring is all about. Who is mature enough to appreciate superb engineering. Who is eager to accept both the thrills and the responsibilities of power motoring allied to superb roadholding. In the hands of such a man the TR6 is one of the most responsive sports cars in the world. At any price.

Engine—In line, overhead valve. 6 cylinder, 152 cu. in. (2498 cc). Bore 2.94 in. (74.7 mm). Stroke 3.74 in. (95 mm). Compression ratio 8.5:1. Full flow oil filter.

Transmission—4 forward speed all synchromesh gear box. Diaphragm type 8½" hydraulically operated clutch. Hypoid final drive bevelled gears in cast iron case rubber mounted on chassis.

Chassis—Channel steel with cruciform bracing. Steel disc type $15'' \times 5\frac{1}{2}''$ wheels. Radial ply red band tires, 185 SR 15.

Suspension—Front: Low periodicity independent system incorporating anti-roll bar. Coil springs and telescopic dampers. Rear: Semi trailing arm independent with coil springs and piston type dampers. All rubber mounted.

Steering—Triumph rack and pinion. Energy absorbing column. 3½ turns lock to lock.

Brakes—Vacuum power independent system. 10%" caliper operated discs—front. 9" drums—rear.

Electrics—Negative ground 12 volt system. 57 amp. hours battery. Twin windtone horns. Two speed electric windshield wipers. Electric windshield washers. Twin back-up lights. Front and rear marker lights. Alternator.

Body—Two seater, two door sports car. Roll-up windows. Rust proofed steel body. Laminated windshield with high impact interlayer. Front hinged safety hood. Locking trunk with courtesy light. Full anti-burst door locks. One either-side-up key for door and ignition.

Top—Zip down rear window panel. Soft top—vinyl inside and out. Reflective safety striping around top. Soft top boot cover. Velcro strips on soft top and cant rails.

Exterior Accourrements — Wrap around bumpers, front and rear. External door mounted rear view mirror. Sealed beam headlights. Magnetic fuel tank cap—6 lb. pressure.

Cockpit—Internal dipping safety rear view mirror. Bucket seats with integral head restraints. Padded swivelling sun visors. Ambla upholstery, perforated on seat facings. Locking glove compartment with courtesy light. 5" 140 mph speedometer with resettable trip milometer. 5" tachometer. Separate fuel, water temperature, oil pressure gauges, and ammeter. Variable intensity dash illumination, blue light. Combined ignition lock accessory control, and starter control. Self cancelling turn signals. Vents for fresh air ventilation at face and foot level. Heating and demisting fresh air system. Leather covered 15" steering wheel rim and matching gear shift knob. Non-glare walnut finish dash. 4-way hazard flasher. Quick release seat belts with stowage holster on outside. Door operated courtesy light.

Spare and Tools—Wheel changing equipment. Spare wheel and tire.

Optional Equipment—Laycock de Normanville overdrive. Operated on 2nd, 3rd, and top gears. Reduces standard 3.70 final drive ratio to 3.03 for smoother, quieter, more economical high speed running.

The Triumph TR6 conforms to Federal Motor Vehicle Safety Standards at the date of manufacture.



One of the world's great car makers
—serving all Canada

BRITISH LEYLAND MOTORS CANADA LIMITED Box 5033, 4445 Fairview Street, Burlington, Ont. Halifax Montreal Burlington Winnipeg Vancouver YOUR DEALER:

Travelling Overseas? Enquire about our Overseas Delivery Service which brings great advantages to Canadian residents travelling aboad.